

**CAT6 UTP OUTDOOR CABLE:**

Cat6 UTP Outdoor cable constructed with 4-pair, conductor is 23 AWG. Available in 500 Mtr per Drum.

**SPECIFICATION:**

Cable Category	Category 6
Cable Construction	U/UTP
Sheath	PVC / LSZH
Overall Length (m)	500
Conductor Material	Solid Bare Copper
Conductor Size (mm)	0.56±0.005mm
Number of Pairs	4
Conductor Gauge (AWG)	23
Insulation	Polyolefin
Outer Jacket	Heavy-duty, black, UV-resistant PE compound for outdoor use.
Package Type	Drum
Temperature operating range	-20 to +60C
Installation temperature range	0 to +50C
Characteristic Impedance	1-250 MHz

DC Resistance	93.0 Ohm/Km max.
Resistance unbalance	2% max.
Capacitance	56 pF/m max. @ 1 KHz
Capacitance Unbalance	1600 pF/m max. @ 1 KHz
Velocity of Propagation (NVP)	67-69%
Dielectric strength	1500 Volts/1 minute

## **FEATURES:**

- Cat6 UTP Outdoor LAN Cable
- 4 twisted pairs
- 23AWG cable diameter
- PVC outer jacket
- ANSI/TIA/568.2-D
- Cable Characteristic Impedance up to 250 MHz.

## **ORDERING INFORMATION:**

<b>DESCRIPTION</b>	<b>PART NUMBER</b>
Cat6 UTP Outdoor Cable, PVC, 500 Mtr	KN-C6UOPVC-500
Cat6 UTP Outdoor Cable, LSZH, 500 Mtr	KN-C6UOLSC-500

## **HEAD QUARTERS:**

BARTYCKA 22B M21A 00-716  
 WARSZAWA, POLAND.

For more information visit us at  
[www.korekonekt.com](http://www.korekonekt.com)