

1000M SINGLE PORT INDUSTRIAL MEDIA CONVERTER (POE SWITCH): (KL-1R1FIMC-GE)



DESCRIPTION:

The KL-1R1FIMC-GE is a 10/100/1000M industrial PoE fiber switch. It has 1*10/100/1000M PoE port and 1*1000M SFP port, Port 1 can support IEEE 802.3af/at PoE standard, single port PoE power up to 30W, the maximum PoE output power is 18W (at-36W). As a PoE power supply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable. It can supply power to POE terminal equipment such as wireless AP, web camera, VoIP phone, industrial sensor through network cable, and meet the network environment that needs high-density PoE power supply. It is suitable for intelligent transportation, rail transit, electric power, mining, metallurgy and green energy. Industrial scenes such as construction set up a cost-effective and stable communication network. Unmanaged model, plug and play, no configuration, easy to use.

PRODUCT DETAILS:

- 1*10/100/1000M PoE port+ 1*1000M SFP port Industrial PoE Switch, port 1 support IEEE 802.3af/at;
- PoE port support AF/AT intelligent recognition. Standard power is 15.4W/port, Maximum power: 30W/port;
- PoE default: 1, 2(+)/3, 6(-), alternative: 4, 5(+)/7, 8(-);
- Switching capacity:8Gbps, MAC table:8K;
- Input voltage: DC48-57V, Redundant dual power 5-bit industrial terminals;
- IP protection level: IP40; Rail-type installation;
- 5 years warranty.

TECHNICAL SPECIFICATIONS:

Model	KL-1R1FIMC-GE
Interface	1*10/100/1000Base-T PoE port (Data/Power) 1*1000Base-X uplink SFP fiber slot port (Data) 2 set of V+, V- redundant DC power interface (5Pin Phoenix terminal)
POE Port	Port 1
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u 100Base-TX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000Base-X; IEEE802.3x

PoE Standard	IEEE802.3af/at	
Ethernet Port Feature	Port 1 support 10/100/1000Base-T, auto-sensing, Full/half duplex MDI/MDI-X self-adaption	
SFP Port	Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)	
Forwarding Mode	Store and Forward (Full Wire Speed)	
Switching Capacity	8Gbps	
Forwarding Rate@64byte	2.98Mbps	
MAC	8K	
Buffer Memory	1M	
Jumbo Frames	10K	
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP (≤100 meter) 100BASE-TX: Cat5 or later UTP (≤100 meter) 1000BASE-T: Cat5e or later UTP (≤100 meter)	
Optical Fiber Cable	Multi-mode: 850nm 0~550M; single mode: 1310nm 0~40KM, 1550nm 0-120KM.	
Power Supply Pin	Default:1/2 (+), 3/6 (-) optional: 4/5(+),7/8(-)	
Working Voltage	48-57VDC; 5P industrial phoenix terminal, anti-reverse protection.	
Max Power Per Port	30W; IEEE802.3af/at	
Total PWR / Input Voltage	18W/48VDC (IEEE802.3af)	36W/48VDC (IEEE802.3at)
Power Consumption	Standby:<4W; Full load:<18W	Standby:<5W; Full load:<32W
LED Indicator	Power: PWR (green), Network: Link, Link/Act (yellow), PoE: PoE (green)	
Power Supply	No, optional 48V/24W or 48V/36W industrial power supply	
Operation TEMP / Humidity	-40~+80°C;5%~90% RH Non condensing	
Storage TEMP / Humidity	-40~+85°C;5%~95% RH Non condensing	
Dimension (L*W*H)	119*100*30mm	
Net /Gross Weight	<0.3kg/<0.5kg	
Installation	Desktop, 35mm DIN rail	
Lightning protection / protection level	<p>Lightning protection: 6KV 8/20us; Protection level: IP40 IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-3(RS):10V/m(80~1000MHz) IEC61000-4-4(EFT): power cable: ±4kV; data cable: ±2kV IEC61000-4-5(Surge): power cable:CM±4kV/DM±2kV; data cable: ±4kV IEC61000-4-6(radio frequency transmission):10V(150kHz~80MHz) IEC61000-4-8(power frequency magnetic field):100A/m;1000A/m, 1s to 3s IEC61000-4-9(pulsed magnet field):1000A/m IEC61000-4-10(damped oscillation):30A/m 1MHz IEC61000-4-12/18(shockwave):CM 2.5kV, DM 1kV IEC61000-4-16(common-mode transmission):30V; 300V, 1s FCC Part 15/CISPR22(EN55022): Class A IEC61000-6-2(Common Industrial Standard)</p>	

Mechanical Properties	IEC60068-2-6 (anti vibration), IEC60068-2-27 (anti shock), IEC60068-2-32 (free fall)
Warranty	5 years.

HEAD QUARTERS:

BARTYCKA 22B M21A 00-716
WARSAWA, POLAND.

For more information visit us at
www.korekonect.com