

**MULTI LOOSE TUBE MICRO CABLE:**



**DESCRIPTION:**

Single Mode Multi loose Micro Cable G.652D &G.657A up to 144 Fibers. Available in 6, 8 & 12 Tubes each cable.

**PRODUCT DETAILS:**

- Micro duct cabling air-blowing system application.
- Each PBT tube containing up to 12 optical fibers.
- HDPE, UV stabilized outer jacket.
- No water leakage.

**SPECIFICATIONS:**

**For 6 Tubes:**

Cable	Fibers	Fibers/Tube	Total Tubes	Diameter
6T x 2F	12	2	6	5.4±5% mm
6T x 4F	24	4	6	5.4±5% mm
6T x 6F	36	6	6	5.4±5% mm
6T x 8F	48	8	6	5.4±5% mm
6T x 10F	60	10	6	5.4±5% mm
6T x 12F	72	12	6	5.4±5% mm

**For 8 Tubes:**

Cable	Fibers	Fibers/Tube	Total Tubes	Diameter
8T x 4F	32	4	8	6.4±5% mm
8T x 6F	48	6	8	6.4±5% mm
8T x 8F	64	8	8	6.4±5% mm
8T x 10F	80	10	8	6.4±5% mm
8T x 12F	96	12	8	6.4±5% mm

**For 12 Tubes:**

Cable	Fibers	Fibers/Tube	Total Tubes	Diameter
12T x 4F	48	4	12	8±5% mm
12T x 6F	72	6	12	8±5% mm
12T x 8F	96	8	12	8±5% mm
12T x 10F	120	10	12	8±5% mm
12T x 12F	144	12	12	8±5% mm

**OPTICAL PARAMETERS:**

Minimum bend radius: 20 x cable  
 UV color fiber: Standard chromatogram  
 Operation Temperature: -430C~ +60C

**ORDERING INFORMATION:**

DESCRIPTION	PART NUMBER
Micro Cable, 6 Tube, 12-72 Fiber, SM	KN—FSM6TMC-XXF
Micro Cable, 8 Tube, 32-96 Fiber, SM	KN—FSM8TMC-XXF
Micro Cable, 12 Tube, 48-144 Fiber, SM	KN—FSM12TMC-XXXF

**XXX- No. of Cores****HEAD QUARTERS:**

BARTYCKA 22B M21A 00-716  
 WARSZAWA, POLAND.

For more information visit us at  
[www.korekonekt.com](http://www.korekonekt.com)